

ShivaShade

Undo

Suture Begone 9060

Shivashade
2025 Merrick Rd
Merrick NY 11566
516-665-8323

1 - Chemical Product and Company Identification

<i>Product Name</i>	Undo Suture Begone 9060	<i>Product Type</i>	Cured Adhesive Remover
<i>Date Revised</i>	12/31/2012	<i>Emergency Number</i>	800-535-5053

2 - Composition/Information on Ingredients

<i>Hazardous Component</i>	<i>CAS Number</i>	<i>%</i>
Organic Ester	proprietary	> 80

<i>Ingredients which Have Exposure Limits</i>	<i>ACGIH (TLV)</i>	<i>OSHA (PEL)</i>	<i>OTHER</i>
<i>Exposure Limits (TWA)</i> Organic Ester	Not established	Not established	

3 - Hazards Identification

<i>Toxicity:</i>	Can cause moderate eye irritation, tearing, and redness. Can cause slight skin irritation. Although no appropriate human or animal health effects data are known to exist, this material is not expected to be an inhalation hazard. No significant signs or symptoms of any health hazard are expected to occur as a result of ingestion.
------------------	--

4 - First Aid Measures

<i>Ingestion:</i>	If large quantity is swallowed, give lukewarm water if victim is completely alert. Do not induce vomiting. Obtain emergency medical attention.
<i>Inhalation:</i>	If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
<i>Skin Contact:</i>	Thoroughly wash exposed areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.
<i>Eye Contact:</i>	Flush eyes with large amounts of water, lifting upper and lower lids occasionally. Get medical attention.

5 - Fire Fighting Measures

<i>Flash Point:</i>	> 250°F, Method: (PMCC)
<i>Flammable Limits % by Volume</i>	LEL: Not Estab. UEL: Not Estab.
<i>Extinguishing Media:</i>	Alcohol foam, water fog, carbon dioxide, or dry chemical

<i>Unusual Fire or Explosion Hazards:</i>	Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition source at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
---	---

<i>Special Fire Fighting Procedures:</i>	Wear self-contained breathing apparatus with a full-face piece operated in pressure-demand or other positive pressure mode when fighting fires.
--	---

<i>Hazardous Products Formed by Fire or Thermal Decomposition:</i>	May form toxic chemicals: Carbon dioxide and carbon monoxide, various hydrocarbons, etc.
--	--

6 - Accidental Release Measures

<i>Steps to be taken in case of spill or leak:</i>	Small Spill: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material and transfer to container. Large Spill: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area or spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, and pump liquid to a salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.
--	---

7 - Handling and Storage

<i>Safe Storage:</i>	Containers of this material may be hazardous when emptied. Since emptied containers retain product residues vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.
----------------------	--

8 - Protective Equipment

<i>Ventilation:</i>	Local Exhaust: Provide sufficient mechanical: (general and/ or local exhaust) ventilation to maintain exposure below level of overexposure (from known , suspected, or apparent adverse effects).
<i>Respiratory Protection:</i>	If overexposure has been determined or documented, a NIOSH/ OSHA jointly approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/ OSHA respirators under specified conditions.
<i>Skin:</i>	Wear resistant gloves such as neoprene, and normal work clothing covering arms and legs.
<i>Eye Protection:</i>	Chemical splash goggles in compliance with OSHA regulations are advised: however, OSHA regulations also permit other type safety glasses.

9 - Physical and Chemical Properties

<i>Appearance:</i>	Clear liquid
<i>Odor:</i>	Characteristic
<i>Boiling Point:</i>	>400°F @ 760 mm Hg
<i>Vapor Pressure:</i>	< .05 mm Hg @ 68°F
<i>Vapor Density:</i>	Unavailable
<i>Evaporation Rate:</i>	Slower vs. n-butyl acetate
<i>Specific Gravity:</i>	>1.0 @ 68°F
<i>Solubility in Water:</i>	Soluble
<i>VOC Content (EPA Method 24):</i>	< 1% by volume

10 - Stability and Reactivity

<i>Stability:</i>	Stable
<i>Hazardous</i>	Not expected to occur.
<i>Incompatibility:</i>	Strong oxidizing agents

11 - Toxicological Information

See section 3

12 - Ecological Information

No data available.

13 - Disposal Considerations

<i>Disposal Procedures:</i>	Small Spill: Dispose of material in accordance with EPA and Local Regulations Large Spill: Destroy by Liquid Incineration.
-----------------------------	---

14 - Transportation Information

Domestic Ground Transport:

This product is not regulated or defined as a Hazardous Material by the DOT, IATA or the IMO. No special paperwork to ship this product worldwide.

15 - Regulatory Information

US Federal Regulations:

<i>TSCA 8b Inventory Status:</i>	n/a
<i>CERCLA/SARA Section 302 EHS:</i>	n/a
<i>CERCLA/SARA Section 311/312:</i>	n/a
<i>CERCLA/SARA 313:</i>	n/a

International Regulations:

<i>Inventory Status:</i>	n/a
<i>Canada DSL/NDSL</i>	Listed
<i>WHMIS Hazard Class:</i>	n/a
<i>EINECS:</i>	Listed
<i>DSL:</i>	Listed

State and Local Regulations:

<i>CA Proposition 65:</i>	None
---------------------------	------

16 - Other Information

<u>Hazard:</u>	<u>NFPA Hazard Code</u>	<u>HMIS Hazard Code</u>
<i>Health:</i>	1	1
<i>Fire:</i>	1	1
<i>Reactivity:</i>	0	0
<i>Specific Hazard:</i>	N/A	Personal Protection; See Section 8

NFPA is a registered trademark of the National Fire Protection Association.
HMIS is a registered trademark of the National Paint and Coatings Association.

Prepared by: Cyberbond Regulatory Department
Company: Cyberbond LLC
401 N Raddant Road
Batavia, IL 60510
630.761.8900 tel
630.761.8989 fax

