

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity**

Dryene Basic

**Alternate Names**

Cauterant Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

Cauterant

**Application Method**

See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

The Dodge Company, Inc  
9 Progress Road  
Billerica, MA 01821

**Emergency**

**CHEMTREC (USA)**

(800) 424-9300

**Customer Service**

**The Dodge Company, Inc**

(800) 443-6343, (978) 600-2099

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 2;H225

Highly Flammable liquid and vapor.

Acute Tox. 3;H301

Toxic if swallowed.

Acute Tox. 5;H313

May be harmful in contact with skin. (Not adopted by US OSHA)

Skin Corr. 1B;H314

Causes severe skin burns and eye damage.

Eye Dam. 1;H318

Causes serious eye damage.

Muta. 2;H341

Suspected of causing genetic defects.

STOT SE 1;H370

Causes damage to organs.

STOT RE 2;H373

May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2;H411

Toxic to aquatic life with long lasting effects.

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



### Danger

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H313 May be harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H341 Suspected of causing genetic defects.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

#### [Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

#### [Response]:

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P307+311 IF exposed: Call a POISON CENTER or doctor / physician.

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



P308+313 IF exposed or concerned: Get medical advice / attention.

P310 Immediately call a POISON CENTER or doctor / physician.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P363 Wash contaminated clothing before reuse.

P370+378 In case of fire: Use alcohol resistant foam, CO2, powder, water spray for extinction. Do not use water jet.

P391 Collect spillage.

### [Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
<b>Methanol</b> CAS Number: 0000067-56-1	50 - 75	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370	[1][2]
<b>Phenol</b> CAS Number: 0000108-95-2	25 - 50	Muta. 2;H341 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT RE 2;H373 Skin Corr. 1B;H314	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 4. First aid measures

#### 4.1. Description of first aid measures

##### General

Move victim to fresh air.  
Call 911 or emergency medical service.  
Give artificial respiration if victim is not breathing.  
Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.  
Administer oxygen if breathing is difficult.  
Remove and isolate contaminated clothing and shoes.  
In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.  
Wash skin with soap and water.  
In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.  
Keep victim warm and quiet.  
Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed.  
Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

##### Inhalation

Move victim to fresh air. Call emergency medical care. Apply artificial respiration if victim is not breathing. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Administer oxygen if breathing is difficult.

##### Eyes

Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart and seek medical attention.

##### Skin

Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Keep victim warm and quiet. Keep victim under observation.

##### Ingestion

If the person is conscious, have him drink water or milk. Contact a physician immediately. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### Overview

INHALATION: Causes irritation of the mucous membranes. Can cause dizziness, nausea, visual impairment, respiratory failure, muscular incoordination, and narcosis.  
SKIN: Phenol is rapidly absorbed through skin. Causes burns, poisoning through skin, and dermatitis.  
EYE CONTACT: Liquid is corrosive to eyes. May cause corneal damage or blindness. Vapors can cause redness and irritation.  
INGESTION: Poisonous. Causes burning in mouth and throat, stomach pain, diarrhea, dizziness, headache and blindness. Can cause death.  
Chronic Overexposure: Poisoning by prolonged exposures to low concentrations of phenol

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



vapors and mists 1) may result in digestive disturbances, nervous disorders, and skin eruptions, and 2) can cause damage to kidneys, and liver. May be fatal. Chronic overexposure to methanol may cause eye damage in humans.

### **Speed in removing phenol is of primary importance**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

#### **Inhalation**

Causes damage to organs.

#### **Eyes**

Causes serious eye damage.

#### **Skin**

May be harmful in contact with skin. (Not adopted by US OSHA) Causes severe skin burns and eye damage.

#### **Ingestion**

Toxic if swallowed.

## 5. Fire-fighting measures

### **5.1. Extinguishing media**

Dry chemical, foam or carbon dioxide.

### **5.2. Special hazards arising from the substance or mixture**

Carbon Monoxide and Carbon Dioxide

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Use explosion-proof electrical / ventilating / light / equipment.

Do not breathe mist / vapors / spray.

### **5.3. Advice for fire-fighters**

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

**HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames.

Vapors may form explosive mixtures with air.

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



Vapors may travel to source of ignition and flash back.

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Vapor explosion and poison hazard indoors, outdoors or in sewers.

Those substances designated with a **(P)** may polymerize explosively when heated or involved in a fire.

Runoff to sewer may create fire or explosion hazard.

Containers may explode when heated.

Many liquids are lighter than water.

TOXIC; may be fatal if inhaled, ingested or absorbed through skin.

Inhalation or contact with some of these materials will irritate or burn skin and eyes.

Fire will produce irritating, corrosive and/or toxic gases.

Vapors may cause dizziness or suffocation.

Runoff from fire control or dilution water may cause pollution.

**ERG Guide No.** 131

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Vapor is heavier than air and may flow along surface to distant ignition source and flashback.

CALL Emergency Response Telephone Number on Shipping Paper first. If Shipping Paper not available or no answer, refer to appropriate telephone number listed on the inside back cover.

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions.

Keep unauthorized personnel away.

Stay upwind.

Keep out of low areas.

Ventilate closed spaces before entering.

Absorb with suitable material and containerize for disposal with a RCRA-approved waste disposal facility.

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 7. Handling and storage

#### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: This substance is not compatible with strong oxidizing agents, acetyl bromide, alkylaluminum solutions, beryllium hydride, boron trichloride, with carbon tetrachloride and metals, chloroform and sodium or sodium hydroxide, cyanuric chloride, dichloromethane and air, diethylzinc, hydrogen and raney nickel catalyst.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingestion	Source	Value
0000067-56-1	Methanol	OSHA	TWA 200 ppm (260 mg/m <sup>3</sup> )
		ACGIH	TWA: 200 ppm STEL: 250 ppm Skin
		NIOSH	TWA 200 ppm (260 mg/m <sup>3</sup> ) ST 250 ppm (325 mg/m <sup>3</sup> ) [skin]
		Supplier	No Established Limit
0000108-95-2	Phenol	OSHA	TWA 5 ppm (19 mg/m <sup>3</sup> ) [skin]
		ACGIH	TWA: 5 ppm Skin
		NIOSH	TWA 5 ppm (19 mg/m <sup>3</sup> ) C 15.6 ppm (60 mg/m <sup>3</sup> ) [15-minute] [skin]
		Supplier	No Established Limit

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### Carcinogen Data

CAS No.	Ingestion	Source	Value
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-95-2	Phenol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

### 8.2. Exposure controls

#### Respiratory

Not necessary where area is properly ventilated.

#### Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

#### Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Wear PVC or rubber gloves.

#### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

#### Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

**Appearance**

Yellow to amber Liquid

**Odor**

Highly perfumed and phenolic

**Odor threshold**

Not Measured

**pH**

N.A.

**Melting point / freezing point (°C)**

Not Measured

**Initial boiling point and boiling range (°C)**

156 - 160F (69 - 71C)

**Flash Point**

56 - 60F (13 - 16C)

**Evaporation rate (Ether = 1)**

Partial > 1 (Bu Acetate=1)



# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 1.7 (methanol) <b>Upper Explosive Limit:</b> 36 (methanol)
<b>Vapor pressure (Pa)</b>	138 mm Hg (methanol)
<b>Vapor Density</b>	Greater than 1
<b>Specific Gravity</b>	0.890 - 0.905
<b>Solubility in Water</b>	Complete
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature (°C)</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured
<b>VOC %</b>	71%

### 9.2. Other information

No other relevant information.

## 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Extreme heat may cause product to decompose, producing acrid smoke and irritating fumes.

### 10.5. Incompatible materials

This substance is not compatible with strong oxidizing agents, acetyl bromide, alkyl aluminum solutions, beryllium hydride, boron trichloride, with carbon tetrachloride and metals, chloroform and sodium or sodium hydroxide, cyanuric chloride, dichloromethane and air, diethylzinc, hydrogen and Raney nickel catalyst.

### 10.6. Hazardous decomposition products

Carbon Monoxide and Carbon Dioxide

## 11. Toxicological information

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Methanol - (67-56-1)	143.00, Human - Category: 3	15,800.00, Rabbit - Category: NA	128.00, Rat - Category: NA	No data available	64,000.00, Rat - Category: NA
Phenol - (108-95-2)	317.00, Rat - Category: 4	630.00, Rabbit - Category: 3	No data available	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	3	Toxic if swallowed.
Acute Toxicity (skin)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute Toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	---	Not Applicable
Sensitization (skin)	---	Not Applicable
Germ toxicity	2	Suspected of causing genetic defects.
Carcinogenicity	---	Not Applicable
Reproductive Toxicity	---	Not Applicable
Specific target organ systemic toxicity (single exposure)	1	Causes damage to organs.
Specific target organ systemic Toxicity (repeated exposure)	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 12. Ecological information

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa
Phenol - (108-95-2)	3.73, Oncorhynchus gorbuscha	3.29, Ceriodaphnia dubia	46.42 (96 hr), Pseudokirchneriella subcapitata

#### 12.2. Persistence and degradability

There is no data available on the preparation itself.

#### 12.3. Bioaccumulative potential

Not Measured

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 14. Transport information

- 14.1. UN number** UN1992  
**14.2. UN proper shipping name** Flammable liquids, toxic, n.o.s., (Methyl Alcohol/Phenol)  
**14.3. Transport hazard class(es)**

#### DOT (Domestic Surface Transportation)

**DOT Proper Shipping Name** Flammable liquids, toxic, n.o.s., (Methyl Alcohol/Phenol)  
**DOT Hazard Class** 3  
**DOT Label** 3, 6.1  
**UN / NA Number** UN1992  
**DOT Packing Group** II  
**CERCLA/DOT RQ** 414 gal. / 3451 lbs.

#### IMO / IMDG (Ocean Transportation)

**IMDG Proper Shipping Name** Flammable liquids, toxic, n.o.s., (Methyl Alcohol/Phenol)  
**IMDG Hazard Class Sub Class** Not Applicable  
**IMDG Packing Group** II

- 14.4. Packing group** II  
**14.5. Environmental hazards**  
**IMDG** Marine Pollutant: Yes ( Phenol )

**14.6. Special precautions for user**

Not Applicable

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not Applicable

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

**WHMIS Classification** B2 D2B E

**US EPA Tier II Hazards**

**Fire:** Yes

**Sudden Release of Pressure:** No

**Reactive:** No

**Immediate (Acute):** Yes

**Delayed (Chronic):** Yes

**EPCRA 311/312 Chemicals and RQs (lbs) (>0.1%) :**

Methanol ( 5,000.00)

Phenol ( 1,000.00)

**EPCRA 302 Extremely Hazardous (>.1%) :**

Phenol

**EPCRA 313 Toxic Chemicals (>.1%) :**

Methanol

Phenol

**Proposition 65 - Carcinogens (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Developmental Toxins (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Female Repro Toxins (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):**

(No Product Ingredients Listed)

**N.J. RTK Substances (>1%) :**

Methanol

Phenol

**Penn RTK Substances (>1%) :**

Methanol

Phenol

# Safety Data Sheet

## Dryene Basic

SDS Revision Date:

02/05/2014



### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.

H341 Suspected of causing genetic defects.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

**This is the first revision of this SDS format, changes from previous revision not applicable.**

This Safety data Sheet was prepared using information provided by/obtained from the Dodge Chemical Company Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to the product. The Dodge Chemical Company, Inc. expressly disclaim all expressed or implied warranty and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other processes as to the accuracy of and/or sufficiency of such information. This Safety Data Sheet may not be changed or altered in any way without the expressed knowledge and permission of The Dodge Chemical Company, Inc.

End of Document