

MATERIAL SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION

Product identifier : **DRY WASH II**

Product Code(s) : None reported.

Product Use : Sundry chemical.

Chemical Family : Mixture.

Supplier's name and address:
The Dodge Chemical Company (Canada) Ltd.
 1265 Fewster Drive
 Mississauga, Ontario, Canada
 L4W 1A2

Manufacturer's name and address:
 Refer to Supplier

Information Telephone # : (905) 625-0311

24 Hr. Emergency Tel # : (613) 996-6666 (CANUTEC)

SECTION 2 - HAZARDS IDENTIFICATION

Classification : WHMIS classification:
 Class B2 (Flammable Liquids);
 Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material);
 Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

OSHA: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). Hazardous classification:
 Flammable liquid;
 Acute Health Hazard;
 Chronic Health Hazard.

Emergency Overview : Colourless liquid. Solvent odour.
 Danger. Extremely flammable liquid and vapor. Vapor may cause flash fire. POISON! May be fatal or cause blindness if swallowed in sufficient quantities. Harmful if inhaled. Harmful if absorbed through the skin. May cause headache, nausea, dizziness and other symptoms of central nervous system depression. Causes eye irritation. May cause skin irritation. Prolonged overexposure may cause liver and kidney effects. Possible birth defect hazard - contains material that may cause birth defects, based on animal data.

POTENTIAL HEALTH EFFECTS:

Signs and symptoms of short-term (acute) exposure

Inhalation : May cause irritation to the nose, throat and upper respiratory tract. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Affected person could experience a latent period of no symptoms, followed by blurred vision and possibly blindness. In extremely high concentrations, may cause coma, respiratory collapse and death.

Skin : May cause moderate skin irritation. May be absorbed and cause symptoms similar to those for inhalation.

Eyes : Exposure to high vapour concentrations or contact with liquid causes severe irritation, redness, tearing and pain.

Ingestion : Poison, may be fatal or cause blindness if swallowed. May cause severe irritation to the mouth, throat and stomach. Symptoms may include burning pain, vomiting and diarrhea. May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. May be absorbed and cause symptoms similar to those for inhalation. Can not be made non-poisonous.

Effects of long-term (chronic) exposure

: Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin. Prolonged overexposure may cause liver and kidney effects.

Carcinogenic status : See TOXICOLOGICAL INFORMATION, Section 11.

Additional health hazards : Potential teratogen. See TOXICOLOGICAL INFORMATION, Section 11.

Potential environmental effects

: See ECOLOGICAL INFORMATION, Section 12.

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Wt.%</u>
Methanol	67-56-1	1.00 - 5.00
Isopropyl acetate	108-21-4	5.00 - 10.00
Acetone	67-64-1	30.00 - 60.00
Heptanes	64741-63-5	30.00 - 60.00
The following ingredients are only present as part of the 'Heptanes' ingredient:		
n-Heptane	142-82-5	Not available.
Toluene	108-88-3	Not available.

Note: n-Heptane and Toluene are not intentionally added to this product.

SECTION 4 - FIRST AID MEASURES

- Inhalation** : Immediately remove person to fresh air. If breathing stopped, begin artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
- Skin contact** : Immediately flush with plenty of water, while removing contaminated clothing. Get medical attention. Wash contaminated clothing before re-use.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. Obtain medical attention immediately.
- Ingestion** : Call a physician or Poison Control Centre immediately. Induce vomiting ONLY under the direct supervision of qualified medical personnel or a poison control centre. Have victim rinse mouth with water, then give one to two glasses of water to drink. Never give anything by mouth to an unconscious person.
- Notes For Physician** : Treat symptomatically. Immediate medical attention is required. Contains methanol.

SECTION 5 - FIRE FIGHTING MEASURES

- Fire hazards/conditions of flammability** : Extremely flammable liquid and vapour. Will ignite when exposed to heat, flame and other sources of ignition. Vapours are heavier than air and collect in confined and low-lying areas. Vapour can travel considerable distance and flashback to a source of ignition. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure. Product may float, and be re-ignited at the water's surface.
- Flammability classification (OSHA 29 CFR 1910.1200)** : Flammable Liquid Class 1B.
- Oxidizing properties** : None known.
- Explosion data: Sensitivity to mechanical impact / static discharge** : Not expected to be sensitive to mechanical impact. Vapours in the flammable range may be ignited by a static discharge of sufficient energy.
- Suitable extinguishing media** : Dry chemical, foam, carbon dioxide and water fog. Water may be ineffective because it may not cool product below the flashpoint.
- Special fire-fighting procedures/equipment** : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.
- Hazardous combustion products** : Carbon oxides; formaldehyde; Hydrocarbons; other unidentified organic compounds.
- NFPA Rating** : 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious
 : Health: 2 Flammability: 3 Instability: 0 Special Hazards: None.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Restrict access to area until completion of clean-up. Keep all other personnel upwind and away from the spill/release. Individuals involved in the cleanup must wear appropriate personal protective equipment. Refer to protective measures listed in sections 7 and 8.

DRY WASH II

MSDS Revision Date:01/31/2013

Page 3 of 7

- Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.
- Spill response/cleanup** : Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled material with inert, non-combustible absorbent material, such as sand. Pick up and transfer to properly labelled containers. Refer to Section 13 for disposal of contaminated material. Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.
- Special spill response procedures** : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).
US CERCLA Reportable quantity (RQ): Methanol (5000 lbs / 2270 kg); Acetone (5000 lbs / 2270 kg); Toluene (1000 lbs / 454 kg).

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Wear chemically resistant protective equipment during handling. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Do not ingest. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks, and open flames. Ground all equipment during handling. Keep away from bases and incompatibles. Wash thoroughly after handling. Keep containers tightly closed when not in use.
- Storage requirements** : Keep heated solution in covered container until cooled. Store in a cool, dry, well-ventilated area. Store away from incompatible materials. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
- Incompatible materials** : Strong oxidizers, strong acids, nitrates, strong alkalies, acetaldehyde, chlorine, fluorine, ethylene oxide and isocyanates.
- Special packaging materials** : Always keep in containers made of the same materials as the supply container.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits

<u>Ingredients</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Methanol	200 ppm (skin)	250 ppm (skin)	200 ppm	N/Av
Isopropyl acetate	100 ppm	200 ppm	250 ppm	N/Av
Acetone	500 ppm	750 ppm	1000 ppm	N/Av
Heptanes	N/Av	N/Av	N/Av	N/Av
The following ingredients are only present as part of the 'Heptanes' ingredient:				
n-Heptane	400 ppm	500 ppm	500 ppm	N/Av
Toluene	20 ppm	N/Av	200 ppm	300 ppm (Ceiling)

Note: n-Heptane and Toluene are not intentionally added to this product.

Ventilation and engineering measures

- : General mechanical ventilation and local exhaust is recommended for use with this product.
- Respiratory protection** : NIOSH-approved respirators are recommended. Advice should be sought from respiratory protection specialists.
- Skin protection** : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.
- Eye / face protection** : Chemical splash goggles are recommended. A full face shield may also be necessary.
- Other protective equipment** : An eyewash station and safety shower should be made available in the immediate working area. Depending on conditions of use, an impervious apron should be worn.
- General hygiene considerations** : Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid.	Appearance	: colourless
Odour	: solvent	Odour threshold	: N/Av
pH	: N/Av		
Boiling point	: 59°C (138°F)	Specific gravity	: 0.78
Melting/Freezing point	: N/Av	Coefficient of water/oil distribution	: N/Av
Vapour pressure (mmHg @ 20° C / 68° F)	: N/Av	Solubility in water	: Miscible
Vapour density (Air = 1)	: > 1	Evaporation rate (n-Butyl acetate = 1)	: > 1
Volatile organic Compounds (VOC's)	: N/Av	Volatiles (% by weight)	: 100%
Flash point	: - 19°C (- 2.2°F)		
Flash point Method	: TCC	Auto-ignition temperature	: N/Av
Lower flammable limit (% by vol.)	: N/Av	Upper flammable limit (% by vol.)	: N/Av
Flame Projection Length	: N/Av	Flashback observed	: N/Av

Section 10: Stability And Reactivity

Stability and reactivity	: Stable under the recommended storage and handling conditions prescribed. Product may form carbon monoxide on standing in direct sunlight. May slowly hydrolyze in the presence of water to Isopropanol and Acetic acid.
Hazardous polymerization	: Hazardous polymerisation does not occur.
Conditions to avoid	: Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances.
Materials To Avoid And Incompatibility	: Strong oxidizers, strong acids, nitrates, strong alkalies, acetaldehyde, chlorine, fluorine, ethylene oxide and isocyanates.
Hazardous decomposition products	: Isopropanol and acetic acid. Refer to Section 5 for additional 'Hazardous combustion products'.

SECTION 11 - TOXICOLOGICAL INFORMATION

Target organs	: Eyes, skin, respiratory system, nervous system, liver.
Routes of exposure	: <i>Inhalation:</i> YES <i>Skin Absorption:</i> YES <i>Skin & Eyes:</i> YES <i>Ingestion:</i> YES
Toxicological data	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	LC₅₀(4hr)	LD₅₀	
	inh, rat	(Oral, rat)	(Rabbit, dermal)
Methanol	64,000 ppm	5628 mg/kg	15,800 mg/kg
Isopropyl acetate	17,100 ppm	6160 - 7380 mg/kg	> 17,490 mg/kg
Acetone	30,000 ppm	5800 mg/kg	> 15,800 mg/kg
Heptanes	> 5000 mg/m ³	> 5000 mg/kg	> 2000 mg/kg
The following ingredients are only present as part of the 'Heptanes' ingredient:			
n-Heptane	25,000 ppm	> 15,000 mg/kg	N/Av
Toluene	7585 ppm	5580 mg/kg	12,125 mg/kg

Carcinogenic status	: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.
Reproductive effects	: Not expected to have other reproductive effects.
Teratogenicity	: Contains methanol, which may cause teratogenic effects at doses which are not maternally toxic. Contains Toluene. Toluene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data.
Mutagenicity	: Not expected to be mutagenic in humans.
Epidemiology	: Not available.

DRY WASH II

MSDS Revision Date:01/31/2013

Page 5 of 7

- Sensitization to material** : Not expected to be a skin or respiratory sensitizer.
Synergistic materials : N/Av
Irritancy : Moderate eye irritant. Mild skin irritant
other important hazards : None known or reported by the manufacturer.
Conditions aggravated by overexposure : Pre-existing skin and respiratory disorders.



SECTION 12 - ECOLOGICAL INFORMATION

- Ecotoxicity** : There is no data available for this product. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.
Mobility : No data is available on the product itself.
Persistence : No data is available on the product itself.
Bioaccumulation potential : No data is available on the product itself.
Other Adverse Environmental effects : No data is available on the product itself.

SECTION 13 - DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7.
Methods of Disposal : Improper disposal can cause damage to the environment. Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.
RCRA : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14: TRANSPORT INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Heptanes; Acetone)	3	II	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDGR, refer to Section 1.17 for additional exemption information, if shipping under this exemption.				
49CFR/DOT	UN1993	Flammable Liquids, n.o.s. (Contains: Heptanes; Acetone)	3	II	
49CFR/DOT Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Refer to 49 CFR Section 173.150. US CERCLA Reportable quantity (RQ): Acetone (5000 lbs / 2270 kg); Methanol (5000 lbs / 2270 kg); Toluene (1000 lbs / 454 kg); Benzene (10 lbs / 4.54 kg); n-Hexane (5000 lbs / 2270 kg).				

SECTION 15 - REGULATORY INFORMATION**US Federal Information:**

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

CERCLA Reportable Quantity (RQ) (40 CFR 117.302): Methanol (5000 lbs / 2270 kg); Acetone (5000 lbs / 2270 kg); Toluene (1000 lbs / 454 kg).

DRY WASH II

MSDS Revision Date:01/31/2013

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: Methanol; Toluene.

US State Right to Know Laws:

California Proposition 65: This product contains chemicals known to the State of California to cause cancer and/or reproductive harm. Contains: Toluene.

Other U.S. State "Right to Know" Lists: The following chemicals are specifically listed by individual States: Methanol (CA, MA, MN, NJ, PA, RI); Acetone (CA, MA, MN, NJ, PA, RI); Isopropyl acetate (CA, MA, MN, NJ, PA, RI); Toluene (CA, MA, MN, NJ, PA, RI); n-Heptane (CA, MA, MN, NJ, PA, RI).

International Information:

WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). Refer to Section 2 for a WHMIS Classification for this product.

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

SECTION 16 - OTHER INFORMATION

HMIS Rating	:	* - Chronic hazard	0 - Minimal	1 - Slight	2 - Moderate	3 - Serious
		<i>Health:</i> *2		<i>Flammability:</i> 3		<i>Reactivity:</i> 0

Legend :

- ACGIH: American Conference of Governmental Industrial Hygienists
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- DOT: Department of Transportation
- EPA: Environmental Protection Agency
- HMIS: Hazardous Materials Identification System
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- MA: Massachusetts
- MN: Minnesota
- N/Ap: Not Applicable
- N/Av: Not Available
- NFPA: National Fire Protection Association
- NJ: New Jersey
- NIOSH: National Institute of Occupational Safety and Health
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration
- PA: Pennsylvania
- PEL: Permissible exposure limit
- RCRA: Resource Conservation and Recovery Act
- RI: Rhode Island
- SARA: Superfund Amendments and Reauthorization Act
- STEL: Short Term Exposure Limit
- TDG: Canadian Transportation of Dangerous Goods Act & Regulations
- TLV: Threshold Limit Values
- TWA: Time Weighted Average
- WHMIS: Workplace Hazardous Materials Identification System

DRY WASH II

MSDS Revision Date:01/31/2013

- References** :
1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2009.
 2. International Agency for Research on Cancer Monographs, searched 2010.
 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2010 (Chempendium, HSDB and RTECs).
 4. Material Safety Data Sheet from manufacturer.
 5. US EPA Title III List of Lists - October 2006 version.
 6. California Proposition 65 List - December 18, 2009 version.

<p>Prepared for: The Dodge Chemical Company (Canada) Ltd. 1265 Fewster Drive Mississauga, ON, Canada L4W 1A2 Telephone: (905) 625-0311 Please direct all enquiries to The Dodge Chemical Company (Canada).</p>	
<p>Prepared by: ICC The Compliance Center Inc. http://www.thecompliancecenter.com</p>	

DISCLAIMER OF LIABILITY

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from The Dodge Chemical Company (Canada) Ltd. and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and The Dodge Chemical Company (Canada) Ltd. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and The Dodge Chemical Company (Canada) Ltd.

Preparation Date (mm/dd/yyyy)

: 01/27/2007

Reviewed Date (mm/dd/yyyy)

: 01/31/2013

Revision No.

: 2

Revision Information

: Converted from 9 section format to 16 section format. All sections modified.

END OF DOCUMENT